

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Canceled)
2. (Currently Amended) A gas sensor element as set forth in claim ~~1~~11, further comprising a reference gas cavity into which gasses containing a constant concentration of oxygen molecules are admitted, and wherein the first monitor cell electrode is exposed to said reference gas cavity, and said oxygen monitor cell is responsive to application of a voltage across the first and second monitor cell electrodes to produce a current flowing between the first and second monitor cell electrodes as a function of the concentration of oxygen molecules within the gas cavity.
3. (Original) A gas sensor element as set forth in claim 2, wherein the voltage applied across the first and second pump cell electrodes is controlled so as to bring the current produced by said oxygen monitor cell into agreement with a constant value for adjusting the concentration of oxygen molecules within the gas cavity to the desired value.
4. (Currently Amended) A gas sensor element as set forth in claim ~~1~~11, further comprising a reference gas cavity into which gasses containing a constant concentration of oxygen molecules are admitted, and wherein the first monitor cell electrode is exposed to said reference gas cavity, and said oxygen monitor cell works to produce an electromotive force between the first and second monitor ~~cells~~cell electrodes as a function of the concentration of oxygen molecules within the gas cavity.
5. (Original) A gas sensor element as set forth in claim 4, wherein the voltage applied across the first and second pump cell electrodes is controlled so as to bring the electromotive force produced by said oxygen monitor cell into agreement with a constant value for adjusting the concentration of oxygen molecules within the gas cavity to the desired value.

6. (Currently Amended) A gas sensor element as set forth in claim 11, wherein said sensor cell is responsive to application of a voltage across the first and second sensor cell electrodes to produce a current flowing between the first and second sensor cell electrodes as a function of the concentration of the specified oxygen containing gas within the gas cavity.

7. (Currently Amended) A gas sensor element as set forth in claim 11, wherein said oxygen monitor cell is responsive to application of a voltage across the first and second monitor cell electrodes to produce a current flowing between the first and second monitor cell electrodes, and said sensor cell is responsive to application of a voltage across the first and second sensor cell electrodes to produce a current flowing between the first and second sensor cell electrodes, and wherein a difference between the current produced by said oxygen monitor cell and the current produced by said sensor cell is provided as a sensor output indicating the concentration of the specified oxygen containing gas.

8. (Currently Amended) A gas sensor element as set forth in claim 11, wherein said gas cavity consists essentially of a first chamber and a second chamber which communicate with each other through a given diffusion resistance, and wherein said oxygen pump cell is disposed within the first chamber, and said oxygen monitor cell and said sensor cell are disposed within the second chamber.

9. (Currently Amended) A gas sensor element as set forth in claim 11, further comprising a partition disposed between said oxygen monitor cell and said sensor cell within said gas cavity.

10. (Currently Amended) A gas sensor element as set forth in claim 11, wherein each of the second pump cell electrode and the second monitor cell electrode exposed to said gas cavity is made of a cermet containing main metallic components of Pt and Au, and the second sensor cell electrode exposed to said gas cavity is made of a cermet whose main component is a metal alloy containing Pt and at least one of Rh and Pd.

11. (Currently Amended) A gas sensor element ~~as set forth in claim 1~~, comprising:  
a gas cavity into which gasses consisting essentially of oxygen molecules and a specified oxygen containing gas are admitted through a given dispersion resistance;  
an oxygen pump cell including an oxygen ion-conducting member, a first pump cell electrode, and a second pump cell electrode which is exposed to the gas cavity, said oxygen pump cell being responsive to application of a voltage across the first and second pump cell electrodes to selectively pump oxygen molecules into and out of said gas cavity for adjusting a concentration of the oxygen molecules within said gas cavity to a desired value;  
an oxygen monitor cell including an oxygen ion-conducting member, a first monitor cell electrode, and a second monitor cell electrode which is exposed to the gas cavity, said oxygen monitor cell working to produce an electric signal indicative of a concentration of the oxygen molecules within said gas cavity; and  
a sensor cell including an oxygen ion-conducting member, a first sensor cell electrode, and a second sensor cell electrode which is exposed to said gas cavity, said sensor cell working to produce an electric signal indicative of a concentration of the specified oxygen containing gas within said gas cavity, wherein the second oxygen monitor cell electrode and the second sensor cell electrode have ends oriented to an upstream side of the flow of the gasses within said gas cavity, one of the ends being shifted from the other in the direction a direction of the flow of the gasses by 2 mm or less.

12. (Currently Amended) A gas sensor element ~~as set forth in claim 1~~, comprising:  
a gas cavity into which gasses consisting essentially of oxygen molecules and a specified oxygen containing gas are admitted through a given dispersion resistance;  
an oxygen pump cell including an oxygen ion-conducting member, a first pump cell electrode, and a second pump cell electrode which is exposed to the gas cavity, said oxygen pump cell being responsive to application of a voltage across the first and second pump cell

electrodes to selectively pump oxygen molecules into and out of said gas cavity for adjusting a concentration of the oxygen molecules within said gas cavity to a desired value;

an oxygen monitor cell including an oxygen ion-conducting member, a first monitor cell electrode, and a second monitor cell electrode which is exposed to the gas cavity, said oxygen monitor cell working to produce an electric signal indicative of a concentration of the oxygen molecules within said gas cavity; and

a sensor cell including an oxygen ion-conducting member, a first sensor cell electrode, and a second sensor cell electrode which is exposed to said gas cavity, said sensor cell working to produce an electric signal indicative of a concentration of the specified containing gas within said gas cavity, wherein an interval between a line about which the second monitor cell electrode of said oxygen monitor cell and the second sensor cell electrode of said sensor cell are arranged to be axi-symmetric and a longitudinal center line of a gas path formed upstream of the second monitor cell and the second sensor cell within said gas cavity is 1 mm or less.

13. (Currently Amended) A gas sensor element as set forth in claim 411, further comprising an air-fuel ratio sensor working to measure a concentration of an air-fuel ratio of the gasses, said air-fuel ratio sensor including an oxygen ion-conducting member, a first electrode, and a second electrode attached to surfaces of the oxygen ion-conducting member, the first electrode being exposed to a gas space within which the gasses exist, the second electrode being exposed to a reference gas cavity into which gasses containing a constant concentration of oxygen molecules are admitted.

14. (Canceled)

15. (Currently Amended) A gas sensor element as set forth in claim 411, wherein the gas sensor element has a length extending in the direction of flow of the gasses, and wherein the second monitor cell electrode and the second sensor cell electrode are laid to overlap each other in a thicknesswise direction perpendicular to the length of the gas sensor element.

16. (New) A gas sensor element as set forth in claim 12, further comprising a reference gas cavity into which gasses containing a constant concentration of oxygen molecules are admitted, and wherein the first monitor cell electrode is exposed to said reference gas cavity, and said oxygen monitor cell is responsive to application of a voltage across the first and second monitor cell electrodes to produce a current flowing between the first and second monitor cell electrodes as a function of the concentration of oxygen molecules within the gas cavity.

17. (New) A gas sensor element as set forth in claim 16, wherein the voltage applied across the first and second pump cell electrodes is controlled so as to bring the current produced by said oxygen monitor cell into agreement with a constant value for adjusting the concentration of oxygen molecules within the gas cavity to the desired value.

18. (New) A gas sensor element as set forth in claim 12, further comprising a reference gas cavity into which gasses containing a constant concentration of oxygen molecules are admitted, and wherein the first monitor cell electrode is exposed to said reference gas cavity, and said oxygen monitor cell works to produce an electromotive force between the first and second monitor cell electrodes as a function of the concentration of oxygen molecules within the gas cavity.

19. (New) A gas sensor element as set forth in claim 18, wherein the voltage applied across the first and second pump cell electrodes is controlled so as to bring the electromotive force produced by said oxygen monitor cell into agreement with a constant value for adjusting the concentration of oxygen molecules within the gas cavity to the desired value.

20. (New) A gas sensor element as set forth in claim 12, wherein said sensor cell is responsive to application of a voltage across the first and second sensor cell electrodes to produce a current flowing between the first and second sensor cell electrodes as a function of the concentration of the specified oxygen containing gas within the gas cavity.

21. (New) A gas sensor element as set forth in claim 12, wherein said oxygen monitor cell is responsive to application of a voltage across the first and second monitor cell electrodes to produce a current flowing between the first and second monitor cell electrodes, and said sensor cell is responsive to application of a voltage across the first and second sensor cell electrodes to produce a current flowing between the first and second sensor cell electrodes, and wherein a difference between the current produced by said oxygen monitor cell and the current produced by said sensor cell is provided as a sensor output indicating the concentration of the specified oxygen containing gas.

22. (New) A gas sensor element as set forth in claim 12, wherein said gas cavity consists essentially of a first chamber and a second chamber which communicate with each other through a given diffusion resistance, and wherein said oxygen pump cell is disposed within the first chamber, and said oxygen monitor cell and said sensor cell are disposed within the second chamber.

23. (New) A gas sensor element as set forth in claim 12, further comprising a partition disposed between said oxygen monitor cell and said sensor cell within said gas cavity.

24. (New) A gas sensor element as set forth in claim 12, wherein each of the second pump cell electrode and the second monitor cell electrode exposed to said gas cavity is made of a cermet containing main metallic components of Pt and Au, and the second sensor cell electrode exposed to said gas cavity is made of a cermet whose main component is a metal alloy containing Pt and at least one of Rh and Pd.

25. (New) A gas sensor element as set forth in claim 12, wherein the second oxygen monitor cell electrode and the second sensor cell electrode have ends oriented to an upstream side of the flow of the gasses within said gas cavity, one of the ends being shifted from the other in the direction of the flow of the gasses by 2mm or less.

26. (New) A gas sensor element as set forth in claim 12, further comprising an air-fuel ratio sensor working to measure a concentration of an air-fuel ratio of the gasses, said air-fuel ratio sensor including an oxygen ion-conducting member, a first electrode, and a second electrode attached to surfaces of the oxygen ion-conducting member, the first electrode being exposed to a gas space within which the gasses exist, the second electrode being exposed to a reference gas cavity into which gasses containing a constant concentration of oxygen molecules are admitted.

27. (New) A gas sensor element as set forth in claim 12, wherein the gas sensor element has a length extending in the direction of flow of the gasses, and wherein the second monitor cell electrode and the second sensor cell electrode are laid to overlap each other in a thicknesswise direction perpendicular to the length of the gas sensor element.

28. (New) A gas sensor element as set forth in claim 11, wherein the second pump cell electrode exposed to the gas cavity is of substantially a rectangular shape with shorter opposite sides and longer opposite sides, the longer opposite sides extending in the direction of the flow of the gases.

29. (New) A gas sensor element as set forth in claim 12, wherein the second pump cell electrode exposed to the gas cavity is of substantially a rectangular shape with shorter opposite sides and longer opposite sides, the longer opposite sides extending in the direction of the flow of the gases.